ENGINEERS SURVEYORS BUILDING CODE INSPECTORS MUNICIPAL SERVICES LIGHT-HEIGEL & ASSOCIATES, INC.

A full service provider of Pennsylvania Uniform Construction Code (UCC) services.

Uniform Construction Code

Application Package DEMOLITION PERMIT

East Cameron Township

LOCAL LIGHT-HEIGEL OFFICE CONTACT INFORMATION:

Light-Heigel & Associates, Inc. 142 Main St., P.O. Box 120 Montandon, PA 17850 *Attn: Building Codes* Phone: (570) 524-7742 Fax: (570) 524-7746

FOR ADDITIONAL INFORMATION: Website: <u>www.light-heigel.com</u> E-mail: Permits@light-heigel.com

DEMOLITION PERMIT: Application Requirements

Demolition permits must be obtained from the Municipal UCC Building Code Official prior to the demolition of any existing building or structure. This permit is separate from that required for construction, alteration or renovations of existing buildings.

Note, however, that when a demolition will occur and plans for the replacement building are submitted concurrently, an application for a demolition permit does not have to be submitted. But, if the demolition is not accompanied by a building permit application, application for a demolition permit will be required.

Please note that receipt of a UCC demolition permit does not relieve the permit holder of compliance responsibilities under other state or federal laws and regulations, including **but not limited to:** asbestos remediation, advanced notification to the PA Department of Environmental Protection and the US Environmental Protection Agency of demolition work, historic preservation and the capping of any sewer and water connections.

Any person desiring to demolish a building or structure must:

- Submit an APPLICATION FOR DEMOLITION PERMIT.
- Provide two (2) copies of a site plan detailing the information requested on the permit application form.
- Pay a demolition fee of the amount calculated below.

Demolition Permit Fee Schedule

A. Residential			
Residential Permit Fee	=	\$100.00	
Government Surcharge	+	\$4.50	
Total Permit Fee	=	\$104.50	
B. Non-Residential			
Non-Residential Permit Fee	=	\$200.00	
Government Surcharge	+	\$4.50	
Total Permit Fee	=	\$204.50	

TOTAL PERMIT FEE

Check made payable to: LIGHT-HEIG	EL & ASSOCIATES,	INC.	
FOR OFFICE USE ONLY:			
CHECK #	RECEIVED ON	BY	

=

MUNICIPAL FEE	=	<u>\$5.00 required.</u>		
Make <u>additional</u> check made pa	ayable to	the Municipality: East Can	neron Township	
FOR OFFICE USE ONLY:				
CHECK #		RECEIVED ON	BY	

	APPLICATION FOR DI				
Proposed	Location of Proposed Demolition Work	Street			
Demolition	Number and Name:				
Information (Political subdivision &	City:	Zip Code:	Tax Parcel ID #:		
<u>county</u> names are <u>required</u> .)	Political Subdivision:		County:		
	File Number (if occupancy was approve	d by L&I):			
	Brief description of building or structure	to be demolisl	ned (use, number of stories)		
	Demolition contractor:				
	Address:				
	Phone:				
Site Plan Requirements	 sidewalks, pavement and curbs wh Size and location of any existing b Area to be filled to existing grade a construction. 	than 1/8" =1') r structures to b here they abut p uildings or struc and seeded or to	on pages which are at least 18" x 24 e demolished, distances to property lines roperty lines.	" Each plan and distances to nticipation of new	
Owner/Applicant	· · · · · · · · · · · · · · · · · · ·	ther than own	ner, list owner information, too.		
Information	Applicant (if other than owner	·):	Owner:		
	Name (typed or printed)		Name (typed or printed)	Phone	
	Number		Phone Number	_ 1 101.5	
	Mailing Address:		Mailing Address:		
	OWNER STATEMENT:				
	I/we,[signatures] certify that I/we own the property described above for which this application is made for a UCC demolition permit and that the applicant has my/our approval to demolish this property or act as our agent in the demolition of this property.				
			Date signed:		

DEMOLITION PERMIT GUIDELINES

The following information must be submitted or addressed prior to issuance of a demolition permit:

- Permit application and the required fee
- Two (2) site plans drawn to scale clearly describing the structure(s) being demolished.
- Asbestos shall be removed in accordance with PA Department of Environmental Protection Asbestos Removal Requirements.
- Indicate type of sewer system: onlot, septic system or public sewer.
- Onlot wells to be abandoned shall have the pump removed; the shaft filled with clean stone and permanently capped 12 inches below finished grade.
- Public water service piping must be capped at an approved location and inspected by a Water Authority representative prior to its concealment / backfilling.
- When onlot septic systems are present: (1) all tanks must be pumped, (2) all associated piping must be removed and properly disposed of, and (3) all tanks must be removed and properly disposed of or abandoned in place with holes punched in the tank bottom and filled with clean fill.
- When public sewer is present and the lateral is being abandoned, the lateral must be capped at the public sewer main and must be inspected by a Sewer Authority representative prior to backfilling.
- All excavations outside the street right of way must be filled with suitable uncontaminated material and installed to meet structural fill requirements if the area will be a bearing surface for below or above ground structures or buildings.
- Indicate whether demolition waste materials will be disposed of onsite or offsite. Only uncontaminated soil, rock, stone, gravel, concrete, brick, concrete block debris may remain onsite. All demolition materials removed from the site must be disposed of at an approved facility / site.
- Future construction (if applicable) requires backfilling with approved engineered fill or excavation to virgin soil.
- Identify the type and location of site utilities such as gas, electric, water, cable, telephone, etc. on the site plan.
- Identify if any underground storage tanks (combustible and flammable liquids) are present on the property.
- Notify *PA One Call* at 800-242-1776 at least 3 days prior to start of demolition or excavation.
- No methods of demolition will be permitted which will not inure all phases of such demolition being strictly confined within the limits of the demolition areas, and without hazard to adjacent properties, or to the public.
- Explosives may not be used to demolish any unit of structure.
- Under no circumstances shall any structure be set afire.
- All buildings shall be completely razed. All floor construction over basements shall be removed; interior basement partitions and pieces of solid masonry construction shall be completely removed. All basement, cellar or foundation walls shall be completely removed.
- Masonry basement floors may be cracked and left as part of the backfill if they are more than 18 inches below ground level.

- All basement partitions, furnaces, heating apparatus, piping, gasoline or oil tanks, miscellaneous fixtures and stairways shall be removed from the area of condemnation.
- All sewer lines are to be located, cut and plugged at the property line closest to the service line.
- Verification from all applicable utilities is required to confirm disconnects/shut-offs, etc.
- All rubbish and debris found on the demolition area at the start of the work as well as that resulting from the demolition activities or deposited on the site by others until final inspection and approval shall be removed and legally disposed of by the contractor who shall keep the project area and public right-of-way reasonably clear at all times. Furthermore, the contractor shall remove all the demolition debris from the site each day.
- Backfilling of all subsurface areas shall conform to the following provisions:
 - a. Before starting backfilling operations, the contractor shall have inspected the empty basement with the Inspector.
 - b. No masonry materials larger than eight inches in any dimension will be considered suitable. No combustible material of any kind will be used or permitted in the backfilling. Fill should be hauled in and not gouged from the surrounding terrain.
 - c. Prior to placing the first layer, existing cellar floors and other surfaced areas shall be broken to insure adequate drainage.
- The final 18" to the existing ground level shall be filled with clean dirt that is free of rubble and vegetable matter. The site shall be left in a clean and aesthetic condition with back filled shaped to the level of the surrounding terrain.
- Final grading shall include two inches of topsoil on top of the lot and seeding with approved seed.
- All requirements of the International Building Code pertaining to demolition must be complied with.